

Viewing an Abend-AID XLS Report

To view a Report, enter the command XLS at TSO Ready or ISPF Option 6 to display the Abend-AID XLS Primary Menu. Enter “1” in the Option field to view an Abend-AID XLS Report.

```
----- Abend-AID XLS Primary Menu ----- CSS V7.9.0
OPTION ==> 1_

1 VIEW      - View Abend-AID XLS Reports or Source listings
2 CREATEJCL - Create JCL to invoke Compuware Language Processor(LP)
3 SOURCE    - Create/Format Source Listing files(s)/SHRDIR/Database(s)
4 AAREPORT  - Create/Format Abend-AID XLS Report file(s)/SHRDIR/DB(s)
5 CONTACTS  - Update Contact Information

L LP        - Learn about Compuware Language Processor
D DDIO      - Learn about Source Listing and Report DDIO files
C LEGAL     - Display Full Copyright/Trade Secrets Notice

Copyright (c) 1976-2002, Compuware Corporation. All rights Reserved.
Unpublished - rights reserved under the Copyright Laws of the United
States.

                (800) 538-7822
                Compuware Shared Services

Press ENTER to process or enter END command to terminate

416  @:00.1 02/18
```

If you do not know your department's Report database name, or if your department does not have a Report database, enter "0" in the "Dataset choice" field and enter the Report directory name 'DC.ABENDAID.REPORT.DIR' in the "Abend-AID Shared Directory or Report File" field. A listing of all members in all databases will be displayed.

If you do not know your department's Source database name, or if your department does not have a Source database, enter "0" in the "Dataset choice" field and enter the Source directory name 'DC.ABENDAID.SOURCE.DIR' in the "Source Directory or Listing Files" field.

Note: When specifying the master Report Directory, all members for all Report databases will be listed, but the name of the Report database which contains a particular member will not be displayed unless the command "showdb" is entered on the Report member selection panel. (See following examples.) However, the ability to actually view a specific member will be based on the RACF authority for the database which contains the member.

```

COMPUWARE/VF ENTRY PANEL ----- COPYRIGHT COMPUWARE CORPORATION 1976, 2002.
Command ==>
Dataset choice . 0          (Select 0 - 8, from below, or C for Contact Data)
Member . . . . .          (MVS:jobname, SOURCE:program, or member*)
                          (Use the LNAME command to enter a Long Program Name)

                          Remote
Abend-AID Shared Directory or Report File:      Volume  Server
0 'DC.ABENDAID.REPORT.DIR'
Source Directory or Listing Files:
1 'DC.ABENDAID.SOURCE.DIR'
2
3
4
5
6
7
8

Processing options:          Source browsing options:
Confirm delete . . YES      (Yes or no)          Unit . . . . . SYSDA
Show print setup . YES      (Yes or no)          Blocking . . . 0246
Show source warning YES      (Yes or no, used only for Abend-AID)
Language . . . . . ENGLISH
Local Server SSID .          (Required for Viewing Remote DDIO files)

4B  @:00.1  03/19

```

Next select your job name. (In the following example, a job name of “DUMPIT2” has been selected.)

Please note that you must have RACF authority to the database in which the file is stored.

```

COMPUWARE/VF ----- 'DC.ABENDAID.REPORT.DIR' ----- Row 1 of 18
COMMAND INPUT ==> SCROLL ==> PAGE
Abend-AID DATASET DIRECTORY - Shared Directory

S - View C - Contact Info D - Delete P - Print L - Lock U - Unlock

```

JOBNAME	REPT	NUMBER	JESID	CODE	DATE	TIME	DESC	SIZE(K)
S DUMPIT2		48	J43194	S0CB	21 JUN 2004	13.40.14	JOHN	25
VBXYZ		39	J26288	S0CB	03 DEC 2003	16.08.59	JOHN	25
VAXYZ		38	J26286	S0CB	03 DEC 2003	16.08.50	JOHN	25
TZXYZ		37	J26280	S0CB	03 DEC 2003	16.08.41	JOHN	25
TRXYZ		36	J26255	S0CB	03 DEC 2003	16.08.03	JOHN	25
SYXYZ		35	J25835	S0CB	03 DEC 2003	15.57.36	JOHN	25
DCXYZ		34	J25831	S0CB	03 DEC 2003	15.57.20	JOHN	25
SMXYZ		33	J25829	S0CB	03 DEC 2003	15.57.10	JOHN	25
SUXYZ		32	J25824	S0CB	03 DEC 2003	15.56.57	JOHN	25
STXYZ		31	J25816	S0CB	03 DEC 2003	15.56.47	JOHN	25
SYXYZ		30	J25782	S0CB	03 DEC 2003	15.55.54	JOHN	25
MWXYZ		28	J25205	S0CB	03 DEC 2003	15.41.09	JOHN	25
MVXYZ		27	J25199	S0CB	03 DEC 2003	15.40.57	JOHN	25
IRXYZ		26	J25193	S0CB	03 DEC 2003	15.40.47	JOHN	25
HPXYZ		29	J25189	S0CB	03 DEC 2003	15.40.36	JOHN	25
CRXYZ		25	J25183	S0CB	03 DEC 2003	15.40.24	JOHN	25
ARXYZ		24	J25001	S0CB	03 DEC 2003	15.34.39	JOHN	25

```

:01.9 08/04

```

Enter “0” in the “Select Section” field to initiate the display process. Use PFK7 and PFK8 to scroll backward and forward. If a Source listing is to be merged (Option 6 from the XLS Output Selection Menu) with the Report, specify the Source Directory name ‘DC.ABENDAID.SOURCE.DIR’ in field 1 labeled: “Source Directory or Listing Files”. Alternatively, the name of the departmental or default database in which the Source is stored may be entered.

Note: A Source listing may be merged with a Report only if the program was compiled using the Procedure CXCB37CL or CXCB37C. This can be done either before or after the abend occurs.

CXCB37CL Example:

```
//CXCOB EXEC CXCB37CL,
//  PGMLIB='load.library', <=== Provide Name of Load Library
//  MNBR='member',        <=== Provide Member Name for Load Library
//  USER='xx',            <=== Provide High-Level Node for REPORT database
//  SORC='source.library(member)' <=== Provide Name of Source Library and Member
//SYSIN DD DISP=SHR,DSN=&SORC
```

Note: If the “USER” parameter is not provided, the default REPORT database will be used. When specifying the master Source Directory, the Source will automatically be merged

```
COMPUWARE/VF ----- OUTPUT SELECTION MENU -----
SELECT SECTION ==> 0_

'DC.ABENDAID.REPORT.DIR' REPT.48 DUMPIT2 J43194

 0 or HEADER   - System, job, and client information
 1 or DIAGS    - Diagnostic information
 2 or NSI      - Next Sequential Instruction (location in program)
 3 or TRACE    - Trace of program flow and program attributes
 5 or REGS     - Register contents and PSWs
 6 or PROG     - Program Storage
 7 or PLIST    - Program Listing (XLS only)
 8 or FILES    - Data management control blocks
 9 or IMS      - IMS diagnostic information and PCBs
10 or IDMS     - CA-IDMS diagnostic and status information
11 or DB2      - DB2 diagnostic and status information
12 or SORT     - Current COBOL sort information
13 or DATALOC  - COBOL Data Locator
14 or MQ       - WebSphere MQ diagnostic information
15 or LE       - LE information
16 or EPILOG   - Abend-AID termination information

      Key section number or name and press ENTER.
Or press ENTER to start at top of output and view sections 1 through 5.

4B 00.2 02/23
```

The top of the Report is displayed in the following example.

```
COMPUWARE/VF -----
COMMAND INPUT ==> _ SCROLL ==> PAGE

'DC.ABENDAID.REPORT.DIR' REPT.48 DUMPIT2 J43194
MONDAY 21 JUN 2004 H09.04.01 F01/26/2004 R09.04.01
*****
* Abend - A I D D i a g n o s t i c s *
*****
Copyright (C) 1976, 2002, Compuware Corporation. Unpublished.
Rights Reserved Under The Copyright Laws Of The United States.

Licensed for use at: 000119
STATE OF CALIFORNIA, TEALE DATA CENTER

Online Technical Support available at: frontline.compuware.com

JESID - JOB43194 OPSYS - OS/390 2.10.00 Model - 2084
Job - DUMPIT2 DFSMS/MVS - V2R10M0 CP FMID - HBB7703
Step - STEP1 System - S634
Time - 13.40.15 LE - OS/390 V2R10

Language Processor Interface Release = 07.09.00
Language Processor Post Processor Release = 07.09.00
4B 01.0 02/21
```

The following two screen examples display the statement that caused the error and the definitions of the fields involved in the abend.

```

COMPUWARE/VF -----
COMMAND INPUT ==> _                                SCROLL ==> PAGE

'DC.ABENDAID.REPORT.DIR' REPT.48 DUMPIT2 J43194

    A decimal-divide exception occurred during execution of program DUMPIT2
    . The expected completion code is S0CB.

*****
*                               *
*      Analysis of Error      *
*                               *
*****

The decimal-divide exception occurred in the following statement:

000174          DIVIDE NUMERATOR BY DENOMINATOR GIVING RESULT.

                Current values of fields on abending statement
                Level/Field Name      Picture/Type Offs      Value
                -----
000045      02 NUMERATOR              99              50
000046      02 DENOMINATOR            99              00
000047      02 RESULT                 # 99V99          LOW-VALUES
                -----

```

02/21

```

COMPUWARE/VF -----
COMMAND INPUT ==> _                                SCROLL ==> PAGE

'DC.ABENDAID.REPORT.DIR' REPT.48 DUMPIT2 J43194

*****
*                               *
*      Error Location      *
*                               *
*****

The statement being executed was:

000174          DIVIDE NUMERATOR BY DENOMINATOR GIVING RESULT.

This statement is contained in
the procedure division in program "DUMPIT2".

The program was compiled on 17 MAY 2004 and is 000040A4 bytes long.

It is part of load module DUMPIT2.
The module was loaded from STEPLIB library SYS080.TEST.LOAD.

The module was link edited on 17 MAY 2004 and is 00004CE8 bytes long.

```

02/21

The following screen example is identical to the example on page 3, except the “showdb” command was used to display the databases in which the members reside.

COMPUWARE/VF ----- 'DC.ABENDAID.REPORT.DIR' ----- Row 1 of 18
 COMMAND INPUT ==> showdb SCROLL ==> PAGE
 Abend-AID DATASET DIRECTORY - Shared Directory

S - View C - Contact Info D - Delete P - Print L - Lock U - Unlock

JOBNAME	REPT	NUMBER	JESID	CODE	DATE	TIME	DESC	SIZE(K)
DUMPIT2		48	J43194	S0CB	21 JUN 2004	13.40.14	JOHN	25
VBXYZ		39	J26288	S0CB	03 DEC 2003	16.08.59	JOHN	25
VAXYZ		38	J26286	S0CB	03 DEC 2003	16.08.50	JOHN	25
TZXYZ		37	J26280	S0CB	03 DEC 2003	16.08.41	JOHN	25
TRXYZ		36	J26255	S0CB	03 DEC 2003	16.08.03	JOHN	25
SYXYZ		35	J25835	S0CB	03 DEC 2003	15.57.36	JOHN	25
DCXYZ		34	J25831	S0CB	03 DEC 2003	15.57.20	JOHN	25
SMXYZ		33	J25829	S0CB	03 DEC 2003	15.57.10	JOHN	25
SUXYZ		32	J25824	S0CB	03 DEC 2003	15.56.57	JOHN	25
STXYZ		31	J25816	S0CB	03 DEC 2003	15.56.47	JOHN	25
SYXYZ		30	J25782	S0CB	03 DEC 2003	15.55.54	JOHN	25
MWXYZ		28	J25205	S0CB	03 DEC 2003	15.41.09	JOHN	25
MVXYZ		27	J25199	S0CB	03 DEC 2003	15.40.57	JOHN	25
IRXYZ		26	J25193	S0CB	03 DEC 2003	15.40.47	JOHN	25
HPXYZ		29	J25189	S0CB	03 DEC 2003	15.40.36	JOHN	25
CRXYZ		25	J25183	S0CB	03 DEC 2003	15.40.24	JOHN	25
ARXYZ		24	J25001	S0CB	03 DEC 2003	15.34.39	JOHN	25

02/27

Note: When specifying the master Report Directory, all members for all Report databases will be listed, but the name of the Report database which contains a particular member will not be displayed unless the command “showdb” is entered on the Report member selection panel. However, the ability to actually view a specific member will be based on the RACF authority for the database which contains the member.

The following screen example is identical to the example on page 4, except the Report database names are displayed in response to the “showdb” command issued in the previous example.

Note: To toggle the “showdb” command off, enter “showdb off” in the Command Input area.

COMPUWARE/VF ----- 'DC.ABENDAID.REPORT.DIR' ----- Row 1 of 18
 COMMAND INPUT ==> SCROLL ==> PAGE
 Abend-AID DATASET DIRECTORY - Shared Directory

S - View C - Contact Info D - Delete P - Print L - Lock U - Unlock

JOBNAME	REPT	NUMBER	JESID	CODE	DATE	TIME	DESC	SIZE(K)
DUMPIT2		48	J43194	S0CB	21 JUN 2004	13.40.14	JOHN	25
SOURCE DATABASE: DC.ABENDAID.REPORT.DB								
VBXYZ		39	J26288	S0CB	03 DEC 2003	16.08.59	JOHN	25
SOURCE DATABASE: VB.ABENDAID.REPORT.DB								
VAXYZ		38	J26286	S0CB	03 DEC 2003	16.08.50	JOHN	25
SOURCE DATABASE: VA.ABENDAID.REPORT.DB								
TZXYZ		37	J26280	S0CB	03 DEC 2003	16.08.41	JOHN	25
SOURCE DATABASE: TZ.ABENDAID.REPORT.DB								
TRXYZ		36	J26255	S0CB	03 DEC 2003	16.08.03	JOHN	25
SOURCE DATABASE: TR.ABENDAID.REPORT.DB								
SYXYZ		35	J25835	S0CB	03 DEC 2003	15.57.36	JOHN	25
SOURCE DATABASE: SY.ABENDAID.REPORT.DB								
DCXYZ		34	J25831	S0CB	03 DEC 2003	15.57.20	JOHN	25
SOURCE DATABASE: SY.ABENDAID.REPORT.DB								
SMXYZ		33	J25829	S0CB	03 DEC 2003	15.57.10	JOHN	25
SOURCE DATABASE: ST.SM.ABENDAID.REPORT.DB								

02/21